

AM 300 HH BB – WCH,B1

Series	Type	Options
AM	300	BP CP EM ePM ₁₀ 50% ePM ₁ 55% ePM ₁ 80% CH WCH PHS ED SD
Version		Bypass (standard) Condensate Pump Energy Meter Intake air filter ePM ₁₀ 50% Intake air filter ePM ₁ 55% Intake air filter ePM ₁ 80% * Comfort Heater Water Comfort Heater PreHeating Surface Motor-driven Exhaust Air Damper Motor-driven Intake Air Damper
1. Character		CO HY ICO ICT IPIR IT PIR EHS
H	Horizontal Exhaust	CO ₂ Sensor, wall mounted, L Hygrostat, wall mounted CO ₂ Sensor, integrated (Analog) CO ₂ -/TVOC Sensor, integrated (Analog) Motion Sensor, integrated TVOC Sensor, integrated (Analog) Motion Sensor, wall mounted Electronic Humidity Sensor, integrated
V	Vertical Exhaust	
S	Side Exhaust	
2. Character		
H	Horizontal Intake	
V	Vertical Intake	
S	Side Intake	
3. Character		
B	Inlet Bottom	
DI	Ducted Inlet	
4. Character		
B	Extract Bottom	
DE	Ducted Bottom	
		B1 B2 K L M AO
		BACnet™/IP BACnet™ MS/TP KNX® * LON® * MODBUS® RTU RS485 Airmaster Airlinq® Online

*Special item